

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

BF

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: C07C 17/20, 17/26, 19/08	A1	(11) International Publication Number: WO 95/04021 (43) International Publication Date: 9 February 1995 (09.02.95)
(21) International Application Number: PCT/US94/08524 (22) International Filing Date: 28 July 1994 (28.07.94) (30) Priority Data: 08/099,677 29 July 1993 (29.07.93) US (71) Applicant: ALLIEDSIGNAL INC. [US/US]; 101 Columbia Road, P.O. Box 2245, Morristown, NJ 07962-2245 (US). (72) Inventors: VAN DER PUY, Michael; 32 Joanne Lane, Cheektowage, NY 14227-1344 (US). MADHAVAN, G., V., Bindu; 99 Kings View Road, Amherst, NY 14221 (US). DEMMIN, Timothy, R.; 87 Havenwood Lane, Grand Island, NY 14072 (US). (74) Agent: ALLIEDSIGNAL INC.; Law Dept. (C.A. McNally), 101 Columbia Road, P.O. Box 2245, Morristown, NJ 07962-2245 (US).		(81) Designated States: JP, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>
(54) Title: PROCESS FOR THE PREPARATION OF HYDROFLUOROCARBONS HAVING 3 TO 7 CARBON ATOMS (57) Abstract The invention relates to a process for preparing hydrofluorocarbons of the formulas $CF_3(CH_2CF_2)_nF$ comprising reacting at least one reactant selected from $CCl_3(CH_2CCl_2)_nCl$, $CCl_3(CH_2CF_2)_nCl$ or $CCl_2[(CH_2CF_2)Cl]_2$, where $n=1$ to 3, with hydrogen fluoride at a temperature of from about 25 to about 200 °C.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

-1-

**"PROCESS FOR THE PREPARATION OF HYDROFLUOROCARBONS
HAVING 3 TO 7 CARBON ATOMS"**

5 BACKGROUND OF THE INVENTION

Field of Invention

This invention relates to the preparation of hydrofluorocarbons (HFCs). Specifically, it relates to the
10 manufacture of a family of HFCs of the formula:



HFCs are of current interest due to their potential to
15 replace ozone depleting CFCs and HCFCs which are used in a variety of applications such refrigerants, propellants, blowing agents, and solvents for degreasing, dewaxing, defluxing, and drying. The compound $\text{CF}_3\text{CH}_2\text{CF}_2\text{CH}_2\text{CF}_3$ ($n = 2$) has physical properties (bp 69-70 °C) that make it useful as a solvent, and has been (generically)
20 claimed as such in European Patent Application 431 458 A1, published December 6, 1991 (assigned to Daikin Industries) and has also been specifically mentioned as a solvent in U.S. Application Serial No. 746,273 filed August 15, 1991 (assigned to AlliedSignal Inc.). The compound 1,1,1,3,3,3-Hexafluoropropane ($n = 1$) has
25 physical properties (bp -1 C) which make it attractive as a blowing agent or propellant. It has been claimed as such in EP 381 986 A. The compound $\text{CF}_3(\text{CH}_2\text{CF}_2)_3\text{F}$ is a novel composition. Its bp of approximately 120°C makes it a useful compound for e.g., dewaxing and other solvent applications.

30

There are several literature preparations disclosed for $\text{CF}_3\text{CH}_2\text{CF}_3$ but only one disclosed for $\text{CF}_3\text{CH}_2\text{CF}_2\text{CH}_2\text{CF}_3$. The latter involves the reaction of SF_4 with acetone dicarboxylic acid

-2-

(HOOCCH₂C(O)CH₂COOH) as taught by Bloschitsa et al., J. Org. Chem. USSR English Translation, 1985, 21, 1414.

Prior art preparations of CF₃CH₂CF₃ can be separated into those which involve precursors having no halogens other than fluorine and those which involve the fluorination of chlorinated or brominated precursors. The former type of processes include a) the reaction of SF₄ with propanedicarboxylic acid (J. Am. Chem. Soc., 1960, 82, 543), b) decarboxylation of (CF₃)₂CHCOOH and its salts (Chem. Abstr., 59:15175f), c) from hexafluorothioacetone (Chem. Abstr., 63:483f), and d) the hydrolysis of appropriate precursors including (CF₃)₂CHC(O)C₂F₅ (Chem. Abstr., 92:180603e) and (CF₃)₃CH (Chem. Abstr. 68:48990d). Processes which involve fluorination of precursors include a) fluorination of hexachloropropene, hexachloropropanes (but not CCl₃CH₂CCl₃), or heptachloropropanes with KF (J. Org. Chem., 1963, 28, 112), b) SbF₃ fluorination of BrCF₂CH₂CF₂Br (J. Am. Chem. Soc., 1955, 77, 2783), c) HgF₂ fluorination of CF₃CH₂CCl₃ (J. Am. Chem. Soc., 1946, 68, 496), and d) fluorination of hexachloropropene with HF over a catalyst at 400-500 C which gave CF₃CHClCF₃ as the main product and CF₃CH₂CF₃ also as a product (Chem. Abstr., 115:207499h).

Industry is continuing to search for alternatives to the preparations of CF₃CH₂CF₃ cited above, since they may be undesirable for one or more of the following reasons a) the cost of reactants is relatively expensive, b) yields are less than those desired for commercialization, or c) starting are not presently readily available. For example, one process disclosed in the literature for the preparation of CF₃CH₂CF₂CH₂CF₃ uses a relatively large quantity of SF₄. Because of the cost of SF₄, an alternative process is needed. Accordingly, it is the objective of this invention to provide an economical method for the preparation of telomer compounds of the formula CF₃(CH₂CF₂)_{n-1-3}F using readily available raw materials.

-3-

Summary of the Invention

One embodiment of the invention relates to a process for preparing hydrofluorocarbons of the formula:

- 5 I. $\text{CF}_3(\text{CH}_2\text{CF}_2)_n\text{F}$ wherein $n=1$ to 3
comprising reacting at least one reactant selected from
 $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_n\text{Cl}$, $\text{CCl}_3(\text{CH}_2\text{CF}_2)_n\text{Cl}$ or $\text{CCl}_2[(\text{CH}_2\text{CF}_2)\text{Cl}]_2$ with hydrogen
fluoride at a temperature of from about 25 to about 200°C in the
presence of a fluorination catalyst; wherein the HF is present in
10 at least stoichiometric amounts per mole of reactant.

- Another embodiment of this invention is a two-step process.
In the first step, telomers are formed by reacting carbon
tetrachloride with vinylidene chloride to give $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_n\text{Cl}$ or
carbon tetrachloride with vinylidene fluoride to give
15 $\text{CCl}_3(\text{CH}_2\text{CF}_2)_n\text{Cl}$ or $\text{CCl}_2[(\text{CH}_2\text{CF}_2)\text{Cl}]_2$, where n is typically 1 to 3.
The telomers ($n=1-2$) can optionally be separated into individual
components by distillation. The second step of the process
involves the fluorination of these telomers as described directly
above using HF, preferably in the presence of a fluorination
20 catalyst, such as an antimony(V) halide, at temperatures of about
25 to about 200°C.

DETAILED DESCRIPTION OF THE INVENTION

- In observing compounds which are structurally related to the
25 telomer reactants employed in this invention, we found that such
related reactants such as $\text{CFCl}_2\text{CH}_2\text{CCl}_2\text{CH}_3$ underwent fluorination in
the presence of HF without a catalyst to provide relatively high
yields (i.e. greater than 50%). Unexpectedly, the fluorination of
telomers of $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_n\text{Cl}$ resulted in relatively low yields.
30 The yields were 13% or even as low as 2% or less for some of the
telomers reactants (see examples 5, 6, & 9). Although one can
prepare $\text{CF}_3(\text{CH}_2\text{CF}_2)_n\text{F}$ in the presence of HF alone, because of the
low yields, industry desires a process which has a significantly
higher yield of the products. We discovered that the relatively
35 low yields of the fluorination process can be enhanced

-4-

significantly when the fluorination catalyst is conducted in the presence of a fluorination catalyst. A fluorination catalyst as used herein is any inorganic metal catalyst used for the substitution of fluorine for chlorine on hydrochlorofluorocarbons (compounds containing carbon, chlorine, fluorine and hydrogen), hydrochlorocarbons (compounds containing carbon, chlorine and hydrogen) and chlorofluorocarbons (compounds containing carbon, chlorine and fluorine) or mixtures thereof. Unexpectedly, the yields of the desired fluorinated telomer are greater than 50%, and as high as 80%+).

The fluorination catalysts employed are metal halides. Preferably, they are selected from halides of Sn, Ti, Ta and Sb. Illustrative of such catalysts are metal (IV) halides and metal (V) halides. More preferred catalysts are metal halides wherein the halogen is chlorine, fluorine or a combination thereof. Additional catalysts are selected from SnCl_4 , TiCl_4 , SbF_5 , SbCl_5 or $\text{SbF}_m\text{Cl}_{5-m}$ wherein m ranges from 1 to 4. Both SnCl_4 and TiCl_4 exhibited marked improvement in the yield of fluorinated products relative to HF alone, but the most preferred catalysts are Sb(V) halides, such as SbF_5 , SbCl_5 and $\text{SbF}_m\text{Cl}_{5-m}$, with m= 1 to 4. These catalysts exhibited superior yields, which can allow for lower operating temperatures and provide shorter reaction times than without the catalysts or with less efficient catalyst.

Apparatus for conducting these fluorinations are conventional devices. The apparatus consists of a direct drive stirring, monel autoclave equipped with a condenser for cooling. By-product HCl is vented periodically to maintain a desired operating pressure, e.g. of about 400 psig. Lower operating pressures (e.g. 100-200 psig) may also be used for larger reactors which may have lower pressure ratings. During the venting of HCl, some HF and lower boiling products (e.g., $\text{CF}_3\text{CH}_2\text{CF}_3$, bp -1°C) may be vented simultaneously, particularly at lower operating pressures. Organic starting material and HF may be added under pressure to supply additional reactants for a continuous process.

-5-

When Sb(V) halides are used as the catalyst, it is advantageous to also co-feed chlorine in an amount (e.g. at least about 1 to 20 mole percent of chlorine) sufficient to maintain the antimony salts in the +5 oxidation state, (the latter being more active than antimony (III) halides).

Useful temperatures will depend on the amount and activity of the catalyst used. The temperature should be selected to effect a sufficient yield of the desired product. Useful temperatures range from about 25 to about 225°C, the preferred temperatures being about 75 to about 150°C when these catalysts are employed. With Sb(V) halides, temperatures in the 50-125 C range are useful, 75-100°C being preferred. Temperatures ranging from 125 to 150 C are best for the less active catalysts, such as SnCl₄ and TiCl₄, which are similar to each other in activity.

The amount of HF supplied to the reactor should be at least stoichiometric, i.e., at least about 6 moles HF per mole CCl₃CH₂CCl₃ or at least about 8 moles HF per mole CCl₃CH₂CCl₂CH₂CCl₃. Generally, more HF than stoichiometric is employed so that HF is essentially a solvent for the fluorination reaction. Excessive amounts of HF limit the output of the product for a batch process. Thus 1 to about 10 times the stoichiometric amount is preferred. We have employed quantities of HF corresponding to 3 to 5 times the stoichiometric amounts with good results.

Reaction times are dependent on several factors including catalyst concentration, the type of catalyst, and the temperature. For a batch process, the progress of the reaction can be conveniently monitored by the increase in pressure due to the formation of by-product HCl. Typical reaction times range from a few hours to about one day.

The amount of catalyst used can vary widely. The amount can depend on the catalyst employed, reactants and other process variables. Although relatively low catalyst concentrations are effective (e.g. less than .05 mole per mole organic added), substantial quantities (0.1 to 0.5 mole catalyst per mole of

-6-

organic) may be desirable in order to enhance the reaction rate and consequently improve product output. The more preferred amount of catalyst used is 0.1 to 0.25 mole of catalyst per mole of organic.

5 Although any method may be used for forming the chlorine-containing reactants which are to be fluorinated in the above-discussed process reactants, preferably, these reactants are formed by the reaction of CCl_4 with a vinylidene chloride or vinylidene fluoride (hereafter both are referred to as the vinylidene
10 reactant). The telomerization of vinylidene reactant, preferably, vinylidene chloride can be initiated by several means, but initiation with metal salts, particularly of copper, has distinct advantages for the process of this invention. The copper salts are believed to initiate the reaction by first reacting with CCl_4
15 to produce a trichloromethyl radical which then combines with vinylidene chloride, initiating the telomerization (see for example, Assher and Vofsi, J. Chem. Soc., 1961, 2261 for a discussion of the mechanism). The copper salts also terminate the telomerization by chlorine atom transfer to the growing radical
20 chain. Thus, the chain lengths are shortened considerably, compared to e.g. peroxide initiated telomerizations. For the reactions of interest here, the telomers of 3 to 7 carbons are obtained in sufficient yield for potential commercialization (hereafter a sufficient yield of reactant or product is at least
25 24%, and at least 50% is preferred. Some control of the telomer distribution is possible by controlling the reaction conditions, notably CCl_4 to vinylidene chloride ratios and the type of copper salt used (see for example Belbachir et al., Makromol. Chem. 1984, 185, 1583-1595). Thus, it is possible to obtain $\text{CCl}_3\text{CH}_2\text{CCl}_3$ with
30 very little higher molecular weight telomers. It is considerably more difficult to obtain only one of the higher molecular weight telomers (5-carbon and higher) starting from CCl_4 and vinylidene chloride. However, if only the 5-carbon material is desired, a mixture of primarily 3-carbon and 5-carbon telomers can be
35 obtained (see Example 1), and the 3-carbon material recycled to

-7-

give the 5-carbon telomer by reaction with vinylidene chloride (see Example 2). An analogous procedure can be used to prepare the 7-carbon telomer from the 5-carbon telomer.

A variety of catalysts have been used in telomerization processes. To a large degree, many of these telomerization catalysts, including mixtures thereof, can often be equivalent, and the choice of catalyst depends on cost, availability, and solubility in the reaction medium. For the telomerization reaction of this invention, it was discovered that salts of copper and iron are preferred. Overall, for the reaction of interest here, the more preferred catalysts are cuprous chloride, cupric chloride, or mixtures of the two or cuprous iodide. The amount of catalysts used in the telomerization reaction is at least about 0.1 mmol, and preferably, about 0.1 to about 50 mmol, per mole of saturated halogenated hydrocarbon (e.g., CCl_4 or $\text{CCl}_3\text{CH}_2\text{CCl}_3$) used. At very low concentrations, the reaction rate may be unacceptably slow, and very high catalyst concentrations may be wasteful due to the fact that the solubility limit may have been reached at even lower catalyst to CCl_4 ratios. Consequently, the more preferred amount of catalyst is about 1 to 20 mmol, per mole of saturated halogenated hydrocarbon.

It is also noted that a co-catalyst can be used in the telomerization process. Amines may be employed as co-catalysts, preferably in concentration of 1 to 10 moles per mole of metal catalyst (i.e. copper salt). Such amine co-catalysts include alkanol amines, alkyl amines and aromatic amines, for example ethanolamine, butyl amine, propyl amine, benzylamine, pyridine and the like.

The ratio of CCl_4 to vinylidene reactant will substantially alter the degree of polymerization (average value of n). Thus, for example, if the desired product has only one more $-\text{CH}_2\text{CCl}_2-$ unit than the starting material, the ratio of CCl_4 (or $\text{CCl}_3\text{CH}_2\text{CCl}_3$) to vinylidene chloride should be relatively high (at least about 2, and preferably, about 2 to 5), so that higher molecular weight telomers are minimized. If the desired product has two or more -

-8-

CH_2CCl_2 - units than the starting material (e.g. $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_2\text{Cl}$ from CCl_4), smaller ratios of CCl_4 to vinylidene chloride (about 0.3 to 1) should be used. The same rationale is used for a system employing vinylidene fluoride.

- 5 Useful temperatures for the telomerization reaction range from about 25 to about 225°C, preferably 80 to about 170°C, so that, depending on reactant concentrations and catalyst activity, convenient reaction times will vary from a few hours to about one day. More preferred temperatures are in the 125 to 140°C range.
- 10 Finally a variety of solvents can be used. Any solvent in which the reactants form the desired product in sufficient yield can be used. Illustrative of such are acetonitrile, dimethylsulfoxide, dimethylformamide, tetrahydrofuran isopropanol, and tertiary butanol. We prefer acetonitrile due to
- 15 its low cost, stability, easy recovery via distillation, and ability to dissolve sufficient amounts of inorganic catalyst salts. Primarily for the latter consideration, the amount of solvent is preferably from about one fourth to two thirds of the total volume, and more preferably one third to one half of the
- 20 total volume. Otherwise, the amount of dissolved catalyst may be relatively low, or the output of product per run will be adversely affected due to a dilution effect.

- Having described the invention in detail and by reference to the preferred embodiments thereof, it will be apparent that
- 25 modifications and variations are possible without departing from the scope of the invention defined in the appended claims and illustrative examples.

EXAMPLES

Example 1

30

Preparation of $\text{CCl}_3\text{CH}_2\text{CCl}_3$ and $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_2\text{Cl}$ from CCl_4

- A 750 mL, direct drive stirring autoclave was charged with 75 mL acetonitrile, 75 mL CCl_4 , 40.4 g vinylidene chloride, and 0.1 g of catalyst made up by mixing equal weights of cuprous chloride and cupric chloride dihydrate. The mixture was heated to
- 35

-9-

130-134°C for 18 h, cooled, and poured into 200 mL water. The organic phase was separated, and the aqueous layer extracted with 50 mL CH_2Cl_2 . The combined organic layers were then dried (Na_2SO_4) and concentrated by rotary evaporation to provide 82.7 g of crude product. Distillation at 1 mm Hg gave 68.5 g $\text{CCl}_3\text{CH}_2\text{CCl}_3$ (bp 47-50 °C), 12.1 g $\text{CCl}_3\text{CH}_2\text{CCl}_2\text{CH}_2\text{CCl}_3$ (bp 109-114°C), and 5.5 g pot residue which contained primarily the above material and $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_3\text{Cl}$. The total yield of 3- and 5-carbon materials accounts for 82.5% of the vinylidene chloride added.

10

Example 2

Preparation of $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_2\text{Cl}$ from $\text{CCl}_3\text{CH}_2\text{CCl}_3$

In a manner similar to that described in Example 1, 101 g of $\text{CCl}_3\text{CH}_2\text{CCl}_3$, 75 mL CH_3CN , 42.3 g vinylidene chloride, and 0.75 g of the same catalyst were heated to 130-136°C for 24 h. Distillation of the crude material, obtained after workup, gave 50.3 g recovered $\text{CCl}_3\text{CH}_2\text{CCl}_3$ and 48.5 g of a mixture of primarily $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_2\text{Cl}$ and $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_3\text{Cl}$. Distillation of the latter gave 39.4 g of 98% pure $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_2\text{Cl}$ (57% yield based on unrecovered $\text{CCl}_3\text{CH}_2\text{CCl}_3$).

20

Example 3

Fluorination of a mixture of essentially pure $\text{CCl}_3\text{CH}_2\text{CCl}_3$ with HF and SbF_5 as catalyst

25 A 600 mL, magnetically stirred, monel autoclave fitted with a condenser (maintained at -10°C), was evacuated, cooled to about -40° C, and charged with 7.6 g (0.035 mole) SbF_5 , followed by 64 g (0.255 mole) $\text{CCl}_3\text{CH}_2\text{CCl}_3$, and 100 g (5 mole) HF. The temperature was increased to 125°C and maintained at that temperature for a total of 18 h. During the heating period, pressure in excess of 400 psig was periodically vented to an aqueous KOH scrubber which was attached to two -78°C cold traps. At the end of the heating period, the remainder of the autoclave contents were slowly vented. The cold traps contained 33.4 g colorless liquid which

30

-10-

consisted of 97.9% $\text{CF}_3\text{CH}_2\text{CF}_3$ and 0.5% $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$ for a yield of 85%.

Example 4

5 Fluorination of $\text{CCl}_3\text{CH}_2\text{CCl}_3$ with HF and TiCl_4 as catalyst

In the apparatus described in Example 2, 64.4 g $\text{CCl}_3\text{CH}_2\text{CCl}_3$, 102.5 g HF and 6.9 g (0.036 mole) TiCl_4 heated to 120°C for 22 hours. The cold traps contained 36.1 g material which by GC analysis, contained 13.1% $\text{CF}_3\text{CH}_2\text{CF}_3$ and 69% $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$. No
10 olefinic materials were observed.

Example 5

15 Fluorination of $\text{CCl}_3\text{CH}_2\text{CCl}_3$ with HF and SnCl_4 as catalyst

In the manner and apparatus described in Example 3, 63.5 g $\text{CCl}_3\text{CH}_2\text{CCl}_3$, 101.4 g HF, and 13.5 g (0.052) SnCl_4 were heated to 125°C for 23.5 h. The cold trap contained 41.5 g material, which by GC analysis contained 13.4% $\text{CF}_3\text{CH}_2\text{CF}_3$, 66.3% $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$, and 20.3% $\text{CF}_3\text{CH}_2\text{CFCI}_2$.
20

Example 6

25 Fluorination of $\text{CCl}_3\text{CH}_2\text{CCl}_3$ with HF at 100°C

In the apparatus used in Example 2, 64 g (0.25 mole) $\text{CCl}_3\text{CH}_2\text{CCl}_3$ and 81 g HF (4.05 mole) were heated to 100°C for 22 h. Although $\text{CF}_3\text{CH}_2\text{CF}_3$ was identified as one of the minor products (less than 2% yield), the major volatile products, identified by GC-MS analysis, included partially fluorinated propanes, e.g., $\text{C}_3\text{H}_2\text{Cl}_2\text{F}_4$ and $\text{C}_3\text{H}_2\text{Cl}_4\text{F}_2$, along with some olefinic by-products. This
30 Example shows that HF alone can be used to prepare $\text{CF}_3\text{CH}_2\text{CF}_3$, but the results are inferior to those involving the use of a catalyst (SbF_5 or TiCl_4 or SnCl_4).

Example 7

-11-

Fluorination of $\text{CCl}_3\text{CH}_2\text{CCl}_3$ with HF at 145°C

In the same manner as Example 5, 64 g $\text{CCl}_3\text{CH}_2\text{CCl}_3$ and 76 g HF were heated to 145°C for 23 h. The cold trap contained 30 g crude product which was comprised of a mixture of
5 chlorofluoropropanes as observed in Example 5. 1,1,1,3,3,3-Hexafluoropropane was present to the extent of about one percent.

Example 8

Fluorination of essentially pure $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_2\text{Cl}$ with HF using
10 SbF_5 as catalyst

In the apparatus described in Example 3, SbF_5 (8.5 g, 0.039 mole), 71.7 g (0.206 mole) $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_2\text{Cl}$, and 96.6 g HF (4.83 mole) were heated to 125°C for a total of 18 h. Pressures in excess of 450 psig were vented to the scrubber and cold traps as
15 in Example 3. At the end of the heating period, the temperature was increased to 150°C and the remainder of the autoclave contents were vented. From the KOH scrubber there was obtained 24.5 g of 98.6% pure $\text{CF}_3\text{CH}_2\text{CF}_2\text{CH}_2\text{CF}_3$, while the cold traps contained 3.7 g of 96% pure $\text{CF}_3\text{CH}_2\text{CF}_2\text{CH}_2\text{CF}_3$ for a total yield of 28.2 g (68% yield).

20

Example 9

Fluorination of $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_2\text{Cl}$ with HF

A mixture of 39.4 g (0.11 mole) $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_2\text{Cl}$ and 74.7 g
25 (3.74 mole) HF was heated in an autoclave to 145°C for 3 h. A total of 18.3 g organic material was recovered, which contained only a trace of $\text{CF}_3\text{CH}_2\text{CF}_2\text{CH}_2\text{CF}_3$ as determined by GC-MS analysis. The crude product was a complex mixture.

30

Example 10

Fluorination of a mixture of chlorocarbons, $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_n\text{Cl}$
(n = 1 to 3), with HF and an Sb(V) chlorofluoride catalyst

The catalyst used in this example was prepared by heating 11.7 g SbCl_5 (0.039 mole) and 19.5 g (0.98 mole) HF to 70°C for 1

-12-

hour. The mixture was then cooled to -40°C , and HCl bled off. Organic chlorocarbon (65 g) used in this example was (by GC analysis) comprised of 11.5% $\text{CCl}_3\text{CH}_2\text{CCl}_3$, 74.5% $\text{CCl}_3\text{CH}_2\text{CCl}_2\text{CH}_2\text{CCl}_3$, and 14% $\text{CCl}_3(\text{CH}_2\text{Cl}_2)_3\text{Cl}$. The mixture was then heated to 125°C . An
5 operating pressure of 400-500 psig was used. After the specified reaction time, the contents were vented to the usual scrubber and cold traps. After warming the traps to room temperature, a total of 22.2 g volatile material was obtained. Of this, about 18.6 g was $\text{CF}_3\text{CH}_2\text{CF}_2\text{CH}_2\text{CF}_3$, and 2.5 g was $\text{CF}_3(\text{CH}_2\text{CF}_2)_3\text{F}$. Distillation gave
10 99.4% pure $\text{CF}_3\text{CH}_2\text{CF}_2\text{CH}_2\text{CF}_3$, bp $69-70^{\circ}\text{C}$ (^1H NMR (CDCl_3): symmetrical multiplet centered at δ 2.9; ^{19}F NMR: 63.2 (6 F) and 93.0 (2 F) ppm upfield from CFCl_3), and 94% pure $\text{CF}_3\text{CH}_2\text{CF}_2\text{CH}_2\text{CF}_2\text{CH}_2\text{CF}_3$, bp $115-122^{\circ}\text{C}$ (^1H NMR (CDCl_3): unsymmetrical multiplet at δ 2.4-3.3; ^{19}F NMR: 62.8 (6 F) and 92.5 (4 F) ppm
15 upfield from CFCl_3).

This example demonstrates the successful fluorination of the mixture of chlorocarbons, thus showing that purified materials need not be employed, and also demonstrates the first preparation of $\text{CF}_3(\text{CH}_2\text{CF}_2)_3\text{F}$.

20

Example 11

In the addition reactions involving CCl_4 , vinylidene fluoride may be substituted for vinylidene chloride to make
25 compounds of the formula $\text{CCl}_3(\text{CH}_2\text{CF}_2)_n\text{Cl}$ and/or $\text{CCl}_2(\text{CH}_2\text{CF}_2)_n\text{Cl}$. Vinylidene fluoride is less reactive than vinylidene chloride and somewhat higher ($20-80^{\circ}\text{C}$ higher) temperature and/or longer reaction times are required.

30 Fluorination of these adducts proceeds under conditions similar to those used in the fluorination of $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_n\text{Cl}$ compounds. In this case, however, the stoichiometric amount of HF required is reduced, e.g. 4 moles HF for the fluorination of 1 mole $\text{CCl}_3\text{CH}_2\text{CF}_2\text{Cl}$ to $\text{CF}_3\text{CH}_2\text{CF}_3$.

-13-

An autoclave was charged with 75 mL CCl_4 , 75 mL acetonitrile, 1 g cuprous iodide, and 3 mL pyridine. The autoclave was closed, evacuated briefly to remove air, and charged with 24.3 g vinylidene fluoride. The contents were then heated with stirring to 150°C for 24 hours. The cooled contents were poured into 200 mL water and the phases separated. The aqueous phase was extracted with 25 mL CCl_4 , and the combined organic phases were washed with saturated NaCl solution and dried (Na_2SO_4). Distillation gave 14.3 g (17% yield) of $\text{CCl}_3\text{CH}_2\text{CF}_2\text{Cl}$, boiling point $60\text{--}62^\circ\text{C}$ at 65 mm Hg (purity 98 %). ^1H NMR (CDCl_3): δ 3.85 (t, $J = 12$ Hz); ^{19}F NMR: 51.8 ppm upfield from internal CFCl_3 (t, $J = 12$ Hz).

Example 12

Preparation of $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_n\text{Cl}$ using CuI/pyridine as the catalyst system.

In Examples 1 and 2, an autoclave was used for the preparation of $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_n\text{Cl}$ since, at the reaction temperatures of about 130°C , the pressure is about 120 psig at the beginning of the reaction. By using the catalyst system consisting of cuprous iodide and pyridine, however, the reaction may be conducted at much lower reaction temperatures and at atmospheric pressure.

A 500-mL flask was purged with nitrogen and charged with 2 g CuI, 280 mL carbon tetrachloride, 40 mL acetonitrile, and 50 mL vinylidene chloride. The mixture was stirred and heated to reflux (65°C). Pyridine (6.5 mL) was then added, and reflux was continued for 21 hours. The reaction mixture was cooled, filtered, washed with 100 mL concentrated HCl, and then washed with a mixture of 50 mL saturated aqueous NaCl and 50 mL of 10% aqueous NaOH solution. Distillation gave 55.2 g (35% yield) of $\text{CCl}_3\text{CH}_2\text{CCl}_3$ and 18.7 g $\text{CCl}_3\text{CH}_2\text{CCl}_2\text{CH}_2\text{CCl}_3$ (17 % yield).

-14-

Comparative Example 1

Fluorination of $\text{FCCl}_2\text{CH}_2\text{CCl}_2\text{CH}_3$ with HF

This comparative example shows that the fluorination of a structurally similar material ($\text{FCCl}_2\text{CH}_2\text{CCl}_2\text{CH}_3$) proceeded in good yield under conditions (HF without catalyst) where both $\text{CCl}_3\text{CH}_2\text{CCl}_3$ and $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_2\text{Cl}$ were fluorinated in very poor yield (Examples 5, 6, and 9). An autoclave was charged with 150 g of 75% pure $\text{FCCl}_2\text{CH}_2\text{CCl}_2\text{CH}_3$ (the other identified components were $\text{CCl}_3\text{CH}_2\text{CFC}_2\text{CH}_3$ (4%), $\text{C}_4\text{H}_5\text{Cl}_3\text{F}_2$ (15.5%), $\text{C}_2\text{H}_2\text{Cl}_4$ (2.5%), $\text{C}_2\text{H}_3\text{Cl}_3$ (2.7%)), and 150 g HF. The reaction mixture was heated to 150-160°C for 6-7 hours, during which time the pressure was maintained at 450-500 psig by periodically venting excess pressure (the vented gases were passed through a KOH scrubber, which was connected in sequence to -15°C and -78°C cold traps). The remainder of the contents were then vented. The cold traps contained 60 g of crude product which was 85-90% pure $\text{CF}_3\text{CH}_2\text{CF}_2\text{CH}_3$. The combined crude product from 4 such runs was distilled to give 159 g of 97% pure $\text{CF}_3\text{CH}_2\text{CF}_2\text{CH}_3$ (50% yield).

-15-

WE CLAIM:

1. A process comprising:
contacting 1,2,3-trichloropentafluoropropane and
H₂ over a catalyst selected from the group consisting
of palladium, platinum, ruthenium, rhodium, iridium and
05 mixtures thereof under reaction conditions sufficient
to produce 1,1,2,3,3-pentafluoropropane.
2. The process of claim 1 wherein said contacting
step is conducted in the vapor phase.
3. The process of claim 1 wherein said catalyst
10 is supported on an inert supporting material.
4. The process of claim 3 wherein said catalyst
is palladium supported on carbon.
5. The process of claim 7 wherein said conditions
include temperatures between about 150°C to about 250°
15 C.
6. The process of claim 8 wherein said conditions
include contact times from about 0.1 second to about 2
minutes.
7. The process of claim 1 additionally comprising
20 the step of repassing at least a part of the product
stream containing the 1,1,2,3,3-pentafluoropropane over
the catalyst to produce more 1,1,2,3,3-
pentafluoropropane.
8. The process of claim 1 further comprising the
25 step of:
selectively fluorinating a chlorinated compound
having the formula (III)
 $\text{CCl}_{3-m}\text{F}_m\text{CFClCCl}_{3-m}\text{F}_m$, wherein m is 0 or 1, with HF
in the presence of a second catalyst selected from the
30 group consisting of antimony fluoride, antimony
chloride, antimony chlorofluorides, mercuric oxide and
chromium containing solid catalysts to produce the
1,2,3-trichloropentafluoropropane.

-16-

9. The process of claim 8 wherein said second catalyst is selected from the group consisting of antimony fluoride, antimony chloride, antimony chlorofluoride and mercuric oxide and the fluorination
05 is conducted in the liquid phase.

10. The process of claim 8 wherein said second catalyst is a chromium containing solid and the fluorination is conducted in the vapor phase.

11. The process of claim 8 wherein said
10 chlorinated compound is produced by reacting CCl_4 or CFCl_3 with a two carbon olefin selected from the group consisting of $\text{CFCl}=\text{CF}_2$, $\text{CFCl}=\text{CFCl}$, $\text{CF}_2=\text{CFCH}$ and $\text{CFCl}=\text{CFH}$ in the presence of a Lewis acid selected from the group consisting of AlCl_3 , FeCl_3 , BF_3 and BCl_3 at
15 temperatures below about 50°C .

12. The process of claim 8 wherein said chlorinated compound is produced by chlorinating a compound having the formula (II)

$\text{CH}_2\text{XCFYCH}_2\text{X}$, where X is H, Cl,
20 or F and Y is H or Cl.

13. The process of claim 12 wherein the compound of formula (II) is produced by contacting HF with an unsaturated compound having the formula (I):

$\text{XCH}=\text{CYCH}_2\text{X}$, where X is H, Cl, or F and
25 Y is H or Cl, in either the vapor or liquid phase.

14. A composition of matter having the formula $\text{HCF}_2\text{CHFCF}_2\text{Cl}$.

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 94/08524

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 C07C17/20 C07C17/26 C07C19/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 C07C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP,A,0 522 639 (SOLVAY (SOCIÉTÉ ANONYME)) 13 January 1993 see the whole document ---	1-15
X	US,A,3 651 019 (M. ASSCHER ET AL.) 21 March 1972 see example 9 -----	9-15

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

2 November 1994

Date of mailing of the international search report

14. 11. 94

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+ 31-70) 340-3016

Authorized officer

Bonnevalle, E

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. onal Application No

PCT/US 94/08524

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0522639	13-01-93	BE-A- 1005096 JP-A- 5201892	20-04-93 10-08-93
US-A-3651019	21-03-72	BE-A- 622939	